

SM33

Compact Ride-on Scrubber Dryer



Technical Specifications

HILO 8065

Tanks (Solution / Recovery)	80/80 L
Cleaning Track	650 mm
Theoretic Yield	3900 sqm/hour
Installed Power / Power Supply	1350W / 24V
Protection Degree	IPX3
Autonomy / Energy Consumption	up to 4h / 0.35W sqm
Dimensions (L x W x H)	1320 x 730 x 1225 mm (Mounted Squeegee)
Weight With/Without Batteries	210 / 125 kg
Reverse Corridor	1.8 m
Sound Level	69 dBA
Brushes	2 x Ø13" - 330mm
Brush Motor Rated Power	550W
Vacuum Brush Rotation Speed	225 - 187 Rpm
Load on Brush Adjustable	0-41 kg
Silenced Turbine Rated Power	500W
Vacuum (0 mm orifice)	1526 mm H ² O
Motor Differential Power with brake	300 W
Working/Transfer Speed	0 - 4 / 0 - 6 km/hour
Max. Slope Exceedable	7% - 16% (Work - Ramp)
Gear Motor Power	30 W
Battery Compartment (2x)	375 x 375 x 315 mm
Standard Batteries (2x)	Gel 12V 105/140Ah (C5/C20)
Recomm. Battery Unit Size/Weight.	345x170x285mm / 42.7kg
Dimensions (Pallet included)	1349 x 749 x 1364 mm
Weight Without Batteries	155 kg (including pallet, cardboard)
Weight with/Without (Accessories)	240kg (batteries) / 246kg (Accessories, Packaging)
Low Voltage/Electromagnetic	2014/35/EC / 2014/30/EC

Standard Parts

